

Wattage (W)	Volts	Product Description	Product Code	CCT (K)	ANSI Code	Cap	Rated Life (h)	Candelas	Beam type	Beam 10%	Beam 50%	Length (mm)	Diameter (mm)	EEC	Energy Consumption (kWh)	Outer qty	Model
PAR 36																	
50	12	50PAR36/WFL 12V	93106410	3000	-	screw lugs	2 000	1300	WFL	48X41	36x28	70	113	G	50	12	1
650	120	DWE Q650PAR36/1 120V	93106412	3200	DWE	screw lugs	100	13000	MFL	-	40X30	70	113	G	650	12	1
PAR 56																	
300	245	300PAR56/NSP 240V	93106408	3000	-	GX16	2000	43000	NSP	-	-	127	179	G	300	12	2
300	245	300PAR56/MFL 240V	93106406	3000	-	GX16	2000	15000	MFL	-	-	127	179	G	300	12	2
300	245	300PAR56/WFL 240V	93106407	3000	-	GX16	2000	5000	WFL	-	-	127	179	G	300	12	2
300	230	300PAR56/MFL 230V	93106403	3000	-	GX16	2000	15000	MFL	-	-	127	179	G	300	12	2
300	230	300PAR56/NSP 230V	93106404	3000	-	GX16	2000	46000	NSP	-	-	127	179	G	300	12	2
300	230	300PAR56/WFL 230V	93106405	3000	-	GX16	2000	5800	WFL	-	-	127	179	G	300	12	2
300	12	300PAR56/WFL 12V	93106399**	3000	-	screw lugs	1000	13000	WFL	-	-	119	179	-	-	12	2
300	12	300PAR56 WFL 12V POOL	93106398**	3000	-	screw lugs	1000	13000	WFL	-	-	119	179	-	-	12	2
PAR 64																	
500	230	500PAR64/WFL 230V	93106409	3000	-	GX16	2 000	10300	WFL	42X20	55X32	152	206	G	500	12	7
500	230	CP86 - Q500PAR64/VNSP 230V	93106666	3200	CP86	GX16d	300	240000	VNSP	16x13	10x7	150	204	G	500	6	7
500	240	CP86 - Q500PAR64/VNSP 240V	93106679	3200	CP86	GX16d	300	240000	VNSP	16x13	10x7	150	204	G	500	6	7
500	230	CP87 - Q500PAR64/NSP 230V	93106680	3200	CP87	GX16d	300	140000	NSP	19x16	11x9	150	204	G	500	6	7
500	240	CP87 - Q500PAR64/NSP 240V	93106681	3200	CP87	GX16d	300	140000	NSP	19x16	11x9	150	204	G	500	6	7
500	230	CP88 - Q500PAR64/MFL 230V	93106682	3200	CP88	GX16d	300	65000	MFL	32x19	21x10	150	204	G	500	6	7
500	240	CP88-Q500PAR64/MFL 240V	93106683	3200	CP88	GX16d	300	65000	MFL	32x19	21x10	150	204	G	500	6	7
1000	230	SUPER CP60 EXC VNS 230V	93106669	3200	CP60	GX16d	300	352000	VNSP	20x17	12x9	150	204	G	1000	6	7
1000	240	EXG PAR64/1000W/240V/WFL	93106670	3200	-	GX16d	300	38000	WFL	59X36	44X22	150	204	G	1000	6	7
1000	230	EXG PAR64/1000W/230V/WFL	93106671	3200	-	GX16d	300	38000	WFL	59X36	44X22	150	204	G	1000	6	7
1000	240	CP95 240V	93106672	3200	CP95	GX16d	300	15000	VWFL	125X95	70X70	150	204	G	1000	6	7
1000	230	SUPER CP61 EXD NS 230V	93106674	3200	CP61	GX16d	300	297000	NSP	22x20	14x10	150	204	G	1000	6	7
1000	240	SUPER CP62 EXE MF 240V	93106675	3200	CP62	GX16d	300	138000	MFL	38x20	24x11	150	204	G	1000	6	7
1000	230	SUPER CP62 EXE MF 230V	93106676	3200	CP62	GX16d	300	138000	MFL	38x20	24x11	150	204	G	1000	6	7
1000	240	SUPER CP61 EXD NS 240V	93106677	3200	CP61	GX16d	300	297000	NSP	22x20	14x10	150	204	G	1000	6	7
1000	240	SUPER CP60 EXC VNS 240V	93106678	3200	CP60	GX16d	300	352000	VNSP	20x17	12x9	150	204	G	1000	6	7

Wattage (W)	Volts	Product Description	Product Code	CCT (K)	ANSI Code	Cap	Rated Life (h)	Lumen (lm)	Beam type	Beam 10%	Beam 50%	Operating Position	MPBC	EEC	Energy Consumption (kWh)	Outer qty	Model
CSI / CID / CSS																	
1000	80	CSI1000/PAR64/G38	93106673	3800	CP62	G38	3500	76000	-	18	6	HOR	1 350 000	G	1000	1	-
1000	80	CID1000/G22 99-0222	93117337**	5500	CP61	G22	500	500	-	-	-	U	-	-	-	1	-
1000	80	CSI1000/G22 99-02	93117338	4000	CP60	G22	500	500	-	-	-	U	-	G	1000	1	-
1000	80	CSI1000/PAR64/HR/G38 99-1422	93117339	3350	GFC	G38	3500	3500	-	18	6	HOR	1 350 000	G	1000	1	-
400	100	CSI400 99-0201 TU	93118295	4000	Special	Special	500	3500	-	18	6	VBD		G	400	10	-

** Not CE compliant product



Wattage (W)	Volts	Cap	Product Description	Product Code	Lumens	CCT (K)	LIF Code	ANSI Code	Rated life (h)	Length (mm)	Operating position	EEC	Energy Consumption (kWh)	Outer qty	Model
Projection, Printing, Photography															
1000	120	G38	MBI800/U SBL2 91-9830 CALMAT	93117205	-	3000	-	-	400	175	U	G	800	1	-
1000	120	G38	GRAPHX MBI 400-2000/U/SB 91-9835 CALM	93106667	-	3000	-	-	500	175	U	G	2000	1	-
300	240	G6.35	A1/249 230-240V	93106518**	7200	3400	A1/249	-	50	62	BD	-	-	24	4
150	240	G6.35	A1/248 230-240V	93106519**	3000	3400	A1/248	-	50	62	BD	-	-	24	4
500	240	GY9.5	A1/244 230-240V	93106495	13000	3200	A1/244	-	75	75	BDTH	G	500	24	5
1000	110	Two right-angle lugs	A1/248 230-240V	93117336	-	3000	-	-	400	110	U	G	800	1	-

Wattage (W)	Volts	Cap	Product Description	Product Code	Lumens	CCT (K)	LIF Code	ANSI Code	Rated life (h)	Length (mm)	Operating position	EEC	Energy Consumption (kWh)	Outer qty	Model
Single Ended Tungsten Halogen															
300	24	G6.35	M36 24V 250W GY6.35	93106531**	5750	3000	M36	-	2 000	62	BD	-	-	100	6
300	240	GY9.5	M38 230-240V	93106477	5500	2900	M38	-	2 000	80	BD	G	300	24	7
500	230	GY9.5	M40 230-240V	93106503	8500	2900	M40	-	2 000	84	BD	G	500	24	8

** Not CE compliant product

