



PRODUCT DATASHEET FLASHLIGHT CAR EMERGENCY

FLASHLIGHT CAR EMERGENCY | Outdoor mobiles

Areas of application

- Multifunctional



Product benefits

- 4 operating modes: 1 press: bright light 100 lm, 2nd press: soft light 70 lm, 3rd press: SOS mode, 4th pressing: flashing mode
- The angle of the light beam is adjusted by turning the lens
- 1,5 h of running at full brightness
- Powered by 4 AAA batteries (not included)

Product features

- Glass hammer, seat belt knife
- Sturdy aluminum housing
- Convenient button for switching modes

TECHNICAL DATA

Electrical data

Nominal wattage	1.60 W
-----------------	--------

Photometrical data

Luminous flux	100 lm
Color temperature	6500 K
Light color (designation)	Cool White
Color rendering index Ra	80

Dimensions & Weight

Diameter	33.00 mm
Height	411.00 mm
Product weight	510.00 g

Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Type of protection	IP22
Dimmable	No
LED module replaceable	Not replaceable

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
---------------------------	-----------------------

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854175824	Folding box 1	43 mm x 43 mm x 426 mm	546.00 g	0.79 dm³
4099854175831	Shipping box 24	271 mm x 189 mm x 455 mm	13546.00 g	23.30 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.